





SINALIZAÇÃO VERTICAL

QUANTITATIVOS E NOTA DE SERVIÇO

INTERSEÇÃO DA ERS-020						
PLACAS	DIMENSÃO	LOCALIZAÇÃO		QUANTIDADES		CORES
		LE	LD	PLACAS	SUPORTES	
1.0) REGULAMENTAÇÃO						
 R-1	L=0,50	-	52+420 52+430	02	02	(01)
 R-1	L=0,25	52+435	-	01	01	(01)
 R-2	L=1,00	-	0+145 Ramo B 0+105 Ramo A	02	02	(2a)
 R-2	L=0,50	52+380	-	01	01	(2a)
 40 km/h	ø 1,00	-	0+120 Eixo ERS-020	01	01	(2)
 40 km/h	ø 1,00	52+555 52+555	52+285 52+285 0+010 Ramo D 0+010 Ramo D	06	03	(2)
1.1) REGULAMENTAÇÃO						
 40 km/h FIM DO TRECHO PAVIMENTADO	2,50 X 1,00	-	0+187 Ramo B	01	02	(2b)
2.0) ADVERTÊNCIA						
 PARE	1,00 x 1,00	-	0+160 Eixo ERS-020	01	01	(03)
3.0) INDICATIVAS						
	3,00 x 1,20	-	0+000 Ramo A	01	03	(05)
	3,00 x 1,20	52+540	-	01	03	(17)

INTERSEÇÃO DA ERS-020						
PLACAS	DIMENSÃO	LOCALIZAÇÃO		QUANTIDADES		CORES
		LE	LD	PLACAS	SUPORTES	
3.0) INDICATIVAS						
	3,00 x 1,20	52+460	-	01	03	(17)
3.1) INDICATIVAS						
	2,50 x 1,20	-	52+260	01	02	(17)
3.2) INDICATIVAS						
	1,50 x 0,50	-	52+340	01	02	(13)
4.0) MARCADOR DE ALINHAMENTO						
	0,50 x 0,60	52+550 52+560 52+570 52+580 52+590	0+045 Ramo A 0+050 Ramo A 0+060 Ramo A	08	08	(3a)
5.0) MARCADOR DE PERIGO						
	0,30 x 0,90	-	52+390 0+050 Ramo A	02	02	(3a)
	0,30 x 0,90	-	52+410	01	01	(3a)